VT-REX 1958

Ref.	Ø"	Ø mm	Thickness	Α	В	R mm	Nº waves	0	Grs.
1958	18"	462	5	130	35,5	610	20	8,5	5100
1958	20"	514	5	130	45	610	20	8,5	7500
1958	20"	514	6	130	45	610	20	8,5	8000
1958	22"	568	5	130	48	610	20	8,5	8900
1958	22"	568	6	130	48	610	20	8,5	10000


These blades are recommended for soft soils as it cuts waste perfectly and it penetrates deeply into the ground.

Furthermore, as the blade gradually wears down, it becomes more aggressive, thus guaranteeing a longer working life for the disc.





















Urola, 10 - 20230 Legazpi - Guipúzkoa (Spain) T: +34 943739000 - F: +34 943733527 marketing@bellotaagrisolutions.com



Ground excellence worldwide

BELLOTA







- O1 THE BEST RESIDUE MANAGEMENT: Thanks to the extremely Sharp Blade, cuts the toughest GMO residue.
- **O2 EXCELLENT CLOD-CRUSHING CAPABILITIES** at normal working speeds and yields superior performance in soft soils.
- **LONGER NOTCHES:** Thanks to the unique flute design, as the blade begins to wear, the flutes actually shift, the hills become the valleys and the valleys become the hills.
- **UNIFORMITY:** Homogenous hardness all along the disc and in all the discs we manufacture.

- LIFETIME WARRANTY: Because we are very sure of our production, we guarantee a lifetime warranty for any manufacturing defect.
- NO BREAKAGES: Bellota blades have the best hardnesselasticity-tenacity ratio in the market. The right manufacturing process guarantees a homogenous hardness in all discs but this is not enough. The disc has to be flexible enough to absorb impacts without breaking, providing the disc a longer life span, even in the most severe soil conditions.

